






- top class design and construction.
- high performance solid state converter
- high frequency
- real time PLL frequency control
- low consumption high efficiency
- output: single head or two commutating heads
- CE label

4.0 READY





- 1 x 230 Vac supply 50-60Hz
- Water cooled system
- M4-1 = 1,5 Kva power M4-3 = 3 Kva power
- Working frequency up to 1250 KHz PLL
- mini head ø 70 mm and micro head 55x55 mm available
- accessories and XYZR adjustable stand available



- Microprocessor controlled
- Fully programmable:
 instantaneous power, preheating,
 heating, post heating time,
 cooling down, ...
 - Working programs saving and recalling by keyword or remote
 - Inert gas valves management
 - RS232 communication bus
- Ready to plug IR pyrometer.
 Integrated functions for "spot" or "thermography" temperature measurement and control

WWW.SINERGO.NET



- High efficiency, high ruggedness, long life compact heads
- Robotic use compliant
- Extra flex connection cable with bayonet connectors both sides







 Gold plated standard and special electrodes made by CAD CAM CNC gold plated









SINERGO srl via Laven 5 - factory: Via Cal di Mezzo 1 31049 Valdobbiadene (Treviso) ITALY tel. +39 0423 976409 fax 972482 VAT IT 02313120269 Sinergo® copyright – 2017. Technical data subjected to change without notice. All rights reserved. Reproduction even partial, unauthorized use, forbidden